

Generator set data sheet



Model: C150D5
Frequency: 50 Hz
Fuel type: Diesel
kW rating: 120 Standby
 109 Prime
 32 Continuous
Emissions level: Tier 1

Exhaust emission data sheet:	
Sound performance data sheet:	
Cooling performance data sheet:	
Genset outline:	A053T462 / A053T063

Fuel consumption	Standby				Prime				Continuous			
	kW (kVA)				kW (kVA)				kW (kVA)			
Ratings	120 (150)				109 (136)				32 (40)			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
US gph	2,9	4,8	7,0	9,0	2,4	4,2	6,3	8,2	1,7	2,9	4,0	5,3
L/h	11	18	26,5	34	9	16	24	31	6,5	11	15	20

Engine	Stanby rating	Prime rating	Continuous rating
Engine manufacturer	Cummins Inc.		
Engine model	6BTA5.9-G3A		
Configuration	6-Cylinder		
Aspiration	Turbocharged/ Aftercooled		
Gross engine power output, kWm (bhp)	135 (181)	122 (164)	75 (100)
BMEP at set rated load, kPa (psi)	1836 (266)	1659 (241)	
Bore, mm (in.)	102 (4,02)		
Stroke, mm (in.)	120 (4,72)		
Rated speed, rpm	1500		
Piston speed, m/s (ft/min)	6 (1180)		
Compression ratio	16,5:1		
Lube oil capacity, L (US gal)	16,4 (4,3)		
Overspeed limit, rpm	1800 ±50		

Fuel flow

Maximum fuel flow, L/hr (US gph)	30 (8)
Maximum fuel inlet restriction, kPa (in Hg)	13,55 (4)
Maximum fuel inlet temperature, °C (°F)	70 (158)
Maximum fuel return line restriction, kPa (in Hg)	67,73 (20)

Air

	Standby rating	Prime rating	Continuous rating
Combustion air, CFM (L/s)	305,12 (144)	286,05 (135)	
Maximum air cleaner restriction, kPa (in H ₂ O)	6,23 (25)		
Alternator cooling air, m ³ /min (cfm)	30,84 (1090)		

Exhaust

Exhaust flow at set rated load, CFM (L/s)	828,48 (391)	756,44 (357)	
Exhaust temperature, °C (°F)	578 (1073)	560 (1041)	
Maximum back pressure, kPa (in H ₂ O)	10,16 (40,83)		

Standard set-mounted radiator cooling

Ambient design, °C (°F)	60 (140)		
Fan load, kWm (HP)	8,2 (10,99)		
Coolant capacity (with radiator), L (US gal)	18,5 (4,89)		
Cooling system air flow, m ³ /min (scfm)	306 (10740,6)		
Total heat rejection, MJ/min (Btu/min)	4,05 (3843)	3,78 (3587)	
Maximum cooling air flow static restriction, kPa (in H ₂ O)	0,12 (0,5)		

Optional with TransferSwitch integrated

Nominal Current (A) for 220V at 60°C	500
Insulation Voltage (V) for 220V	1000
Nominal Current (A) for 380V At 60°C	315
Insulation Voltage (V) for 380V	1000

Weights

Unit Open dry weight, kgs	1090
Unit Open wet weight, kgs	1123
Unit Enclosed dry weight, kgs	1457
Unit enclosed wet weight, kgs	1490

Derating factors

Standby	Full rated power available up to 1000 m (3280 ft) elevation at ambient temperature of 40 °C (104 °F). Above these conditions, derate by an additional 4% per 300 m (1000 ft) and 2% per 11 °C (1% per 10 °F). For other temperature and altitude limits, consult your local Cummins distributor.
Prime	Full rated power available up to 1000 m (3280 ft) elevation at ambient temperature of 40 °C (104 °F). Above these conditions, derate by an additional 4% per 300 m (1000 ft) and 2% per 11 °C (1% per 10 °F). For other temperature and altitude limits, consult your local Cummins distributor.
Continuous	Full rated power available up to 1000 m (3280 ft) elevation at ambient temperature of 40 °C (104 °F). Above these conditions, derate by an additional 4% per 300 m (1000 ft) and 2% per 11 °C (1% per 10 °F). For other temperature and altitude limits, consult your local Cummins distributor.

Ratings definitions

Emergency Standby Power (ESP):	Limited-Time Running Power (LTP):	Prime Power (PRP):	Base Load (Continuous) Power (COP):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited-Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) is in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

Alternator data

Voltage	Connection	Temp rise degrees C	Duty¹	Winding No.	Frame Size
220	Wye, 3Phase	150	S/P/C	311	UC274E
380	Wye, 3Phase	150	S/P/C	311	UC274E
400	Wye, 3Phase	150	S/P/C	311	UC274E
440	Wye, 3Phase	150	S/P/C	311	UC274E

Notes:

¹ Standby (S), Prime (P) and Continuous ratings (C).

Formulas for calculating full load currents:

Three phase output

$$\frac{\text{kW} \times 1000}{\text{Voltage} \times 1.73 \times 0.8}$$

Warning: Back feed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device or after building main switch is open.

**For more information contact your local Cummins distributor
or visit power.cummins.com**



Our Energy working for you.™

© 2019 Cummins Inc. All rights reserved. Cummins is a registered trademark of Cummins Inc. PowerCommand, AmpSentry, InPower and "Our energy working for you." are trademarks of Cummins Inc. Other company, product, or service names may be trademarks or service marks of others. Specifications are subject to change without notice.